

SAFETY INSTRUCTIONS

IMPORTANT SAFETY INSTRUCTIONS!

Read and understand all instructions before using the hand tools.
Follow all warnings on product and instructions.

WARNING

Needle sticks can transmit life-threatening diseases if tools are shared.
Use only your own tool and needle.
Protective tagging gloves recommended.
Immediately discard any needle that sticks you (see instructions).

To discard a contaminated needle, immediately:

1. Use adhesive bandage to remove contaminated needle, to avoid contaminating needle guard.
2. Dispose of needle and bandage in an approved Biohazard-Sharps container.*

To reduce the chance of needle sticks:

1. Use a protective tagging glove while tagging.**
2. Put needle guard on needle when not in use, and when installing or removing uncontaminated needles.


Following these warnings are important, because:

1. Invisible traces of infected blood can remain on the needle for days after a needle stick.
2. Someone else could use your hand tool by mistake.
3. A contaminated needle can infect the next person who gets stuck, transmitting HIV, Hepatitis, or other bloodborne diseases.

* For details, see OSHA 3127 and 29 CFR 1910.1030.

** Call for supplier information on protective tagging gloves.

Operating & Safety Instructions for Hand Held Tagging Tools




WARNING: BEFORE USING TOOL, READ IMPORTANT NEEDLE SAFETY PROCEDURES ON BACK COVER. SAVE THESE INSTRUCTIONS WHERE TOOL IS STORED.

IMPORTANT NOTE: It is recommended that the user test the tagging system on each fabric to be tagged because different fabrics require different tagging fasteners and needles.

OPERATING INSTRUCTIONS

Installing & Removing Needles



To install needle

1. Place needle guard over the needle.
2. Place the tool on its side, with the needle lock facing upwards.
3. Turn the pointed needle lock towards the front of the tool.
4. Turn the tool over.
5. Insert needle with its long slot running parallel to the slot in the tool.
6. Once in place, turn the needle lock back towards the rear of the tool. Rotate until horizontal to lock.

To remove the needle*

1. Place the needle guard over the needle.
2. Position the tool on its side, with the needle lock facing up.
3. Turn pointed needle lock towards the front of the tool.
4. Slide the needle out of the tool.
5. Dispose of needle in a biohazard-sharps container.

*For contaminated needles, see safety procedures on back cover.

The EHD Tool (#10778) is equipped with a white "Release Button" on the right side of the tool to assist in removing fastener clips.

To remove a clip from the tool, slide the Release Button towards the front of the tool. With the Button in the forward position, pull the fastener clip out of the tool, then let go of the Button.

Loading Fasteners

To load fasteners

1. Insert the end of the round connecting bar on the fastener clip into the round guide slot at the top of the tool.
2. Gently push the fastener clip into the guide as far as it will go and tool is ready for use.

To remove a partially used clip

PISTOL GRIP TOOL

Fully depress the trigger and remove the clip by pulling upwards.

* Always depress the trigger when removing a clip of fasteners from the tool. Failure to do so may cause the tool to jam.

SCISSOR GRIP TOOL




















Push the release button, located on the side of the tool, down and forward and remove the clip by pulling upwards.

Attaching Fasteners

To attach fasteners


1. Insert the needle through the hole in the tag.
2. Insert the needle through the garment.
3. Hold the material firmly against the front of the tool and squeeze the trigger.
4. Release the trigger.
5. Withdraw the needle and tool from the garment
6. Tag and attachment will be securely fastened to garment.
7. Always use the needle guard when tool is not in use.

SPARE PARTS NUMBER

No.	PART	DRAWING	No.	PART	DRAWING
1			11		
2			12		
3			13		
4			14		
5			15		
6			16		
7			17		
8			18		
9			19		
10					

FOR TAGGING AND LABELING

COMPACT DESIGN




FOR TAGGING AND LABELING

COMPACT DESIGN

1 _____

Insert either end of the fastener connecting bar into the feed slot at top of the gun. Push the clip into the slot as far as it will go. Gun is now ready to use.



2 _____

Insert the needle through the tag hole and fabric. Hold gun firmly against the merchandise and squeeze the trigger fully.




3 _____

Release trigger completely and withdraw the needle. The tag should be securely fastened.



4 _____

To remove a clip of tag fastener, press the Release button upward and pull the clip out of the top of the tagger gun.



5 _____

If a fastener jams, first release the trigger and remove the needle. Carefully remove the jammed fasteners from the gun or needle.



6 _____

To remove or insert the needle, turn the needle lock lever ahead as shown and remove the needle and insert new needle and turn the needle lock lever back.



ENJOY TAGGING WITH THE COMPACT & PRIME QUALITY !